

AMENDMENTS TO THE CLAIMS

Kindly amend claims 2, 3, 6, 10, 12, and 17. Please cancel claims 1, 4-5, 7-9, 13-16, and 18-21. Claims pending in the application become:

1. (Canceled):

2. (Currently Amended): ~~The A supersonic aircraft according to Claim 1 wherein comprising:~~

a fuselage extending forward and aft along a longitudinal axis, the fuselage having a lower surface and an upper surface;

a highly swept low aspect ratio wing coupled to the fuselage, the wing having a forward leading edge and an aft trailing edge;

an effector flap coupled to the wing trailing edge;

a tail empennage coupled to the fuselage aft of the wing on the fuselage upper surface in a position high relative to the wing, the tail empennage forming a channel

region subject to complex shock patterns the tail empennage has and having an

inverted V-tail geometry coupled to the wing in a braced wing configuration

further comprising a vertical stabilizer, lateral inverted stabilizers, and inverted

V-tail control surface ruddervators; and

an effector coupled to the tail empennage; and

a controller coupled to the effector flaps and the effectors, the controller further

comprising a control process that reduces drag through channel relief by

deflecting both the effector flap down and the effector up, and the controller

further comprises a control process capable of adjusting the aircraft

longitudinal lift distribution for a selected supersonic Mach number to

maintain a low sonic-boom, low drag-trim condition.

KOESTNER BERTANI LLP
18662 MACARTHUR BLVD.
SUITE 400
IRVINE, CA 92612
TEL (949) 251-0250
FAX (949) 251-0260

3. (Currently Amended): ~~The A supersonic aircraft according to Claim 1~~
~~wherein comprising:~~
a fuselage extending forward and aft along a longitudinal axis, the fuselage having a
lower surface and an upper surface;
a highly swept low aspect ratio wing coupled to the fuselage, the wing having a
forward leading edge and an aft trailing edge;
an effector flap coupled to the wing trailing edge;
a tail empennage coupled to the fuselage aft of the wing on the fuselage upper surface
in a position high relative to the wing, the tail empennage forming a channel
region subject to complex shock patterns, and having the tail empennage has a
supersonic T-tail geometry further comprising a vertical stabilizer, a lateral
horizontal stabilizer, and a control surface elevator; and
an effector coupled to the tail empennage; and
a controller coupled to the effector flaps and the effectors, the controller further
comprising a control process that reduces drag through channel relief by
deflecting both the effector flap down and the effector up, and the controller
~~further comprises~~ a control process capable of adjusting the aircraft
longitudinal lift distribution for a selected supersonic Mach number to
maintain a low sonic-boom, low drag-trim condition.

4. (Canceled):

5. (Canceled)

6. (Currently Amended): ~~The A supersonic aircraft according to Claim 1~~
~~further comprising:~~
a fuselage extending forward and aft along a longitudinal axis, the fuselage having a
lower surface and an upper surface;
a highly swept low aspect ratio wing coupled to the fuselage, the wing having a
forward leading edge and an aft trailing edge;
an effector flap coupled to the wing trailing edge;
engines coupled to the aft portion of the wing lower surface; and

KOESTNER BERTANI LLP
18462 MACARTHUR BLVD.
SUITE 400
IRVINE, CA 92612
TEL (949) 231-0250
FAX (949) 231-0260

a tail empennage coupled to the fuselage aft of the wing on the fuselage upper surface in a position high relative to the wing, the tail empennage forming a channel region subject to complex shock patterns and an inverted V-tail geometry empennage coupled to the wing in a braced wing configuration and carrying lift at the aft portion of the aircraft on a high mounted tail, the length of the aircraft being effectively lengthened for shock waves below the aircraft, thereby further reducing sonic boom, the inverted V-tail carrying tail lift high to maintain a continuous lift distribution and structurally bracing the wing and engines;

an effector coupled to the tail empennage; and
a controller coupled to the effector flaps and the effectors, the controller further comprising a control process that reduces drag through channel relief by deflecting both the effector flap down and the effector up.

7. (Canceled):

8. (Canceled):

9. (Canceled):

10. (Currently Amended): ~~The A~~ supersonic aircraft according to Claim 7 further comprising:

an aircraft body extending forward and aft;

a highly swept low aspect ratio wing coupled to the body, the wing having a forward leading edge and an aft trailing edge;

an effector flap coupled to the trailing edge of the wing;

an inverted V-tail coupled at the aft portion of the aircraft body and coupled to the wing in a braced wing configuration, the inverted V-tail forming a channel region that can generate complex shock patterns;

two wing-mounted engines positioned beneath the wing at an aft location, the braced wing V-tail supporting the engines and enabling trim for a low sonic boom lift distribution;

KOESTNER BERTANI LLP
18413 MACARTHUR BLVD
SUITE 400
IRVINE, CA 92612
TEL (949) 251-0250
FAX (949) 251-0260

ruddervator control surfaces coupled to the inverted V-tail; and
a controller coupled to the effector flap and the ruddervator control surfaces, the
controller comprising a control process that reduces drag through channel
relief by deflecting both the effector flap down and the ruddervator control
surfaces up.

11. (Original): The aircraft according to Claim 10 wherein:
the engines have a highly integrated wing/inlet geometry that enables low-boom
compatibility and low inlet/nacelle installation drag.

12. (Currently Amended): ~~The A supersonic aircraft according to Claim 7~~
~~wherein comprising:~~

an aircraft body extending forward and aft;
a highly swept low aspect ratio wing coupled to the body, the wing having a forward
leading edge and an aft trailing edge;
an effector flap coupled to the trailing edge of the wing;
an inverted V-tail coupled at the aft portion of the aircraft body and coupled to the
wing in a braced wing configuration, the inverted V-tail forming a channel
region that can generate complex shock patterns;
ruddervator control surfaces coupled to the inverted V-tail; and
a controller coupled to the effector flap and the ruddervator control surfaces, the
controller comprising a control process that reduces drag through channel
relief by deflecting both the effector flap down and the ruddervator control
surfaces up, and the controller further comprises a control process that adjusts
aircraft longitudinal lift distribution for a selected Mach number to maintain a
low sonic boom, low drag-trim condition..

13. (Canceled):

14. (Canceled):

15. (Canceled):

KOESTNER BERTANI LLP
18662 MACARTHUR BLVD.
SUITE 400
IRVINE, CA 92612
TEL. (949) 231-0260
FAX (949) 231-0260

16. (Canceled):

17. (Currently Amended): The A channel control system according to Claim 15 for usage in a supersonic aircraft including a fuselage, wings, a tail empennage, and a plurality of control effectors coupled to the wings and the tail empennage, the empennage and wings forming a channel region that can form complex shock patterns at transonic speeds, the channel control system comprising:

a plurality of actuators coupled to the control effectors, the effectors including a flap coupled to the wing and an effector coupled to the tail empennage; and
at least one vehicle management computer coupled to the plurality of actuators, the at least one vehicle management computer further comprising a process for managing the control effectors in a drag reduction mode through channel relief by deflecting both the flap downward and the tail empennage effector upward,
wherein:

the wing is a highly swept low aspect ratio wing coupled to the body, the wing having a forward leading edge and an aft trailing edge, and an effector flap coupled to the trailing edge of the wing;

the tail empennage is in a configuration of an inverted V-tail coupled at the aft portion of the aircraft body and coupled to the wing in a braced wing configuration, the tail empennage comprising ruddervator control surfaces coupled to the inverted V-tail; and

the at least one vehicle management computer further comprises a channel relief process that reduces drag through channel relief by deflecting both the effector flap downward and the ruddervator upward.

18. (Canceled):

19. (Canceled):

20. (Canceled):

KOESTNER BERTANI LLP
18662 MACARTHUR BLVD.
SUITE 400
IRVINE, CA 92612
TEL (949) 251-0250
FAX (949) 251-0260

21. (Canceled):

KOESTNER BERTANI LLP
18662 MACARTHUR BLVD.
SUITE 400
IRVINE, CA 92612
TEL (949) 231-0210
FAX (949) 231-0260

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.